

## NOTES:

- 1. FOR CATHODIC TEST STATION AT MANHOLE, SEE STD DWG 904.
- 2. PROVIDE WEEPHOLES WHERE WATER TABLE IS BELOW BOTTOM OF PIPE & AS DIRECTED BY OWNER, DO NOT WATERPROOF IF WEEPHOLES ARE PROVIDED.
- 3. WATERPROOF OUTSIDE MANHOLE STRUCTURE WITH CRYSTALLINE AS MANUFACTUERED BY PERMAQUIK OR APPROV. EQUIV.
- 4. 6" MINIMUM DISTANCE FROM TOP OF PIPE OR CROTCH PLATE (SINGLE OR DOUBLE) TO TOP OF CONCRETE BASE.

| REVISION   | DATE                    | BY  | DESCRIPTION                                  | CALLEGUAS MUNICIPAL | STANDARD DRAWINGS | DWG NO |
|--|-------------------------|-----|--|---------------------|-------------------|--------|
| 6<br>7<br>8  | 03/06<br>11/06<br>12/06 | P&d | GENERAL<br>GENERAL<br>GENERAL                | WATER DISTRICT      | MANHOLE ACCESS    | 711A   |
| APPROVED Susan Mulligan Digitally signed by Susan Mulligan DN: ore-Susan Mulligan, c=0 |                         |     | 1 VII III (12 h) DN: on-Queen Mulligen c-110 |                     | STRUCTURE         | '''^   |
|  |                         |     | MANAGER OF ENGINEERING DATE                  | THOUSAND OAKS CALIF | FORNIA            |        |