

NOTES:

1. SEE THE PLANS FOR THE FOLLOWING INFORMATION:
TYPE OF STAIRWAY AND LOCATION
W = WIDTH OF STAIRWAY
L = LENGTH OF LANDINGS
T = LENGTH OF TREAD
R = HEIGHT OF RISER
C = WIDTH OF CURB
S = LENGTH OF STAIRWAY FLIGHT
2. CONCRETE FINISH FOR EXPOSED SURFACES SHALL BE CLASS I, EXCEPT THAT TREADS AND LANDINGS SHALL BE TROWELLED SMOOTH AND GIVEN A FINE BROOM FINISH IN A DIRECTION PERPENDICULAR TO THE CENTERLINE OF THE STAIRWAY. THE BROOM FINISH SHALL BE BROUGHT TO THE NOSE OF THE TREADS AND LANDINGS.
3. ONE HANDRAIL IS REQUIRED FOR STAIRWAYS 4' (1.22 m) WIDE OR LESS. TWO HANDRAILS ARE REQUIRED FOR WIDER STAIRWAYS.

STANDARD PLANS FOR PUBLIC WORKS CONSTRUCTION

REINFORCED CONCRETE STAIRWAY

STANDARD PLAN

640-3

SHEET 2 OF 2