

NOTES:

- 1. UNDER FRAME & COVER THE TOP STEP AND ANY STEPS IN 24" OR 30" RISERS SHALL BE MADE FROM STAINLESS CONFORMING TO ASTM A-276, TYPE 316.
- 2. FOR ALL OTHERS AT 15" STEPS, THE CONTRACTOR SHALL SUBSTITUTE ONE OF THE FOLLOWING STEEL REINFORCED POLYPROPYLENE PLASTIC STEPS (OR APPROVED EQUAL).
- 3. STEPS SHALL BE STEEL CONFORMING TO ASTM 307 AND SHALL BE GALVANIZED AFTER FABRICATION. IF STAINLESS STEEL STEPS ARE SPECIFIED OR CALLED FOR ON PLANS, THE MATERIAL SHALL CONFORM TO ASTM A 276, 300 SERIES.
- 4. BOTTOM STEP SHALL BE MAXIMUM OF 2 FEET ABOVE FLOOR OR SHELF.

MANUFACTURER	STEP I.D.
M.A. INDUSTRIES, INC.	PS2-PFS
OR	
SOUTHWEST CONCRETE PRODUCTS	X038PS

	CITY	OF	RANCHO	CUCAMONGA,	CALIFORN	NIA
APPROVED	BYı			STEEL STEP		STANDARD PLAN
Mulion	ne i o	6.1.92		SIEEL SIEI		325
CITY ENGI	NEER 24953	DATE		SPECIFICATIONS FOR PUBLIC WO	RKS CONSTRUCTION	SHEET 1 OF 1